

# XP-350BM / 350B

Thermal Barcode Printer

## Key features

- Printing speed: Min: 50.8mm/s Max: 152mm/s
- Thermal sensitive resistance, photoelectric sensor
- Serial+USB+Lan interface
- Labels peel off, tear off automatically
- Memory: DRAM: 4M NV FLASH: 4M
- Support PDF417, QR CODE, Data matrix 2D Printing
- Embedded with internet default IP
- 100MB Ethernet interface connection, data transfer efficiency



## Specifications

Model	XP-350BM	XP-350B
Printing method	Direct thermal	
Resolution	203dpi (8dots/mm)	
Printing width	76mm	
Paper width	20~82mm	
Paper roll diameter	25mm ( Min ) for internal, 100mm ( Max ) for external	
Printing length (Max.)	1000mm	
Paper thickness	0.06~0.19mm	
Printing speed	Min: 50.8mm/s Max: 152mm/s	
Print head temperature sensor	Thermal sensitive resistance	
Bar code	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPC-E, UPC-E+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14	
Print head position sensor	Micro switch	
Media type	Paper roll, sticker, label fold, etc.	
QRCODE	PDF417, QR CODE, Data Matrix	
Paper off type	Tear off & peel off	Tear off
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts	
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation	
Gross weight	1.44 kg	
Dimension	220(D) x 148(W) x 150(H)mm	
Work	5~45 , 20~80%RH	
Storage	-40~55 , 93%RH(40 )	
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1	
Input	24VDC, 2.5A	
Paper exists detection	Photoelectric sensor	
Interface	Serial+USB+Lan	USB
Memory	DRAM: 4M; FLASH: 4M	
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM	