



## Thermal Receipt Printer

# XP-E260L




- Horizontal, Wall-hanging design.
- Easy of use feature include drop in paper load and auto cutter.
- Flexibility interface include USB, Serial, ethernet all in one.



# XP-E260L

## Thermal Receipt Printer



| MODEL                  | XP-E260L                                                                                                                                                                                                                                             |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printing method        | Direct thermal                                                                                                                                                                                                                                       |
| Printing speed         | 260mm/s                                                                                                                                                                                                                                              |
| Paper width            | 79.5 ± 0.5mm                                                                                                                                                                                                                                         |
| Printable area         | 72mm(adjustable by commands)                                                                                                                                                                                                                         |
| Maximum paper diameter | Φ80 mm                                                                                                                                                                                                                                               |
| Paper thickness        | 0.06-0.08mm                                                                                                                                                                                                                                          |
| Column capacity        | 576 dots/line 512 dots/line                                                                                                                                                                                                                          |
| Line space             | 3.75mm(Changeable by commands)                                                                                                                                                                                                                       |
| Commands               | Compatible with ESC/POS                                                                                                                                                                                                                              |
| Interface type         | USB+Serial+Lan                                                                                                                                                                                                                                       |
| Character size         | ANK, Font A: 12×24 dots<br>Font B: 9×17 dots<br>simplified/traditional Chinese: 24x24 dots                                                                                                                                                           |
| Dimension              | 192×140×140 mm (D×W×H)                                                                                                                                                                                                                               |
| Gross weight           | 1.12 kg                                                                                                                                                                                                                                              |
| Bar code               | UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128                                                                                                                                                                                   |
| 2-dimension code       | QR CODE / PDF417                                                                                                                                                                                                                                     |
| Code page              | PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251) |
| Cutter                 | Partial                                                                                                                                                                                                                                              |
| Cutter life            | 1.5 million cuts                                                                                                                                                                                                                                     |
| Print head life        | 100KM                                                                                                                                                                                                                                                |
| Input buffer           | 64 Kbytes                                                                                                                                                                                                                                            |
| NV Flash               | 256 Kbytes                                                                                                                                                                                                                                           |
| Power adaptor          | AC110V/220V, 50~60Hz                                                                                                                                                                                                                                 |
| Power source           | DC 24V/2.5A                                                                                                                                                                                                                                          |
| Cash drawer output     | DC 24V/1A                                                                                                                                                                                                                                            |
| Work environment       | Temperature: 0~45°C , humidity: 10~80RH%                                                                                                                                                                                                             |
| Storage environment    | Temperature: -10~60°C , humidity: 10~90RH%                                                                                                                                                                                                           |
| Operating system       | Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux                                                                                                                                                                                                   |



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.poskeytech.com  
Email: overseas@xprinter.net

