

XP-236B

Thermal Barcode Printer

Xprinter®

- Adjustable print speed: Min 50.8mm/s, Max 101 mm/s
- Adjustable paper width: Min 20mm, Max 48mm
- Maximum paper roll diameter: 80mm
- Support QR CODE Printing



Coffee Shop



Shopping




Mart



XP-236B

Thermal Barcode Printer



Model	XP-236B	
Mode	Label print mode	Receipt print mode
Printing Features		
Resolution	203 DPI	203 DPI
Printing method	Direct Thermal	Direct Thermal
Max.print speed	50.8~101 mm/s	90 mm/s
Max.print width	48 mm	48mm
Media		
Media type	Thermal paper/Thermal stickers	Thermal paper
Media width	paper 20~48 mm	48mm
Media roll diameter	Max.80 mm	
Supply method	Easy Paper Loading	
Performance Features		
Memory	DRAM 64Kb Flash 4 MB	
Interfaces	USB/USB+Bluetooth/USB+WiFi	
Sensors	Print head temperature sensor/ Paper end / Cover open / Gap	Print head temperature sensor/ Paper end/ Cover open /
Drawer port	1 ports (Pin 2 for cashdrawer)	
Fonts/Graphics/Symbologies		
Character sizes	Font 0 to Font8	Font A: 12x24, Font B: 9x17, CHN: 24*24
1D barcode	CODE128, EAN128, ITF, CODE39, CODE39C, CODE39S, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5, MSI, MSIC, PLESSEY, ITF14, EAN14	Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D bar code	QR code, PDF-417	QR code
Emulation	TSPL	ESC/POS
Dimension	189*130*135mm (D×W×H)	
Weight	1.08 kg	
Print head life	50 km	
Driver	Windows	Windows/Linux/Mac/Android
SDK	iOS / Android / Windows	
Input	DC 9V/3A	
Environmental Conditions		
Operation	5 ~ 45°C, Humidity: RH 20 ~ 80%	
Storage environment	-40 ~ 55 °C, Humidity: ≤93% RH (40°C)	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

