

XPrinter Thermal Receipt Printer 80mm

Model: XP-N260H



Features:

- Stylish high-end thermal printer 260 mm / sec low noise, high speed printing.
- Standard Chinese simplified GB18030 large character library.
- Simplified / Traditional can be freely converted by instructions.
- 83MM large capacity paper warehouse.
- Low power consumption, low operating costs.
- Support cash box drive.
- With automatic paper cutting features.
- Built-in wall hanging function.
- Support kitchen printing, network printing.
- Support IAP online upgrade, save time and worry.
- Support NVLOGO download image printing (picture format is BMP).
- Support free lost function, prevent lost orders.
- Adopt new Tool return calibration technology, prevent card cutter.
- Support single reminder, error alarm function.
- Support multiple kinds of one-dimensional bar code printing.
- Support QR code (QR code type: QR CODE, PDF417).
- Support energy control, print head overheating protection, the life of the print head is longer.
- The network port interface is 100M network speed, and the data transmission speed is fast.
- Support Linux system, advanced OPOS driver.
- Compatible with ESC/POS command, has strong compatibility.
- Easy loading paper structure, convenient loading Paper with out of paper detection, support for black mark detection.

Specifications:

Print	Printing method	Thermal printing
	Print width	72mm paper width
	Point density	576 points / line or 512 points / line
	Printing speed	260 mm / sec
	Interface type	9P serial port + USB + network port
	Printer paper	79.5 ± 0.5 mm × φ 80 mm
	Line spacing	3.75 mm (can adjust the line spacing with commands)
	Number of columns	80mm paper: 80mm paper: Font A - 42 columns or 48 columns / Font B - 56 columns or 64 columns / simple, traditional - 21 columns or 24 columns
	Character size	ANK character, Font A: 1.5 × 3.0mm (12 × 24 points) Font B: 1.1 × 2.1mm (9 × 17 points) Jane / Traditional: 3.0 × 3.0mm (24 × 24 points)
Bar Code Character	Extended character table	PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2) , PC852 (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251)
	One-dimensional code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
	QR code	QRCode, PDF417
Buffer	Input buffer	64k bytes
	NV Flash	256k bytes
Power supply	Power supply	Output: DC 24V/2.5A
	Cash box output	DC 24V/1A
Physical Characteristics	Weight	1.12 kg
	Dimensions	192 × 140 × 140 mm (depth × width × height)
Environmental Requirements	Working environment	Temperature: 0~45°C, Humidity: 10~80%
	Storage environment	Temperature: -10~60°C, Humidity: 10~90% (no condensation)

Made in China