COMPACT DESIGN, IDEAL FOR C

Thermal Receipt Printer

XP-R330H

- 58mm/80mm/82.5mm paper width available
- IAP function supports firmware update within 5S. Make printer maintained easily.
- Reliable cutter with intelligent code to prevent cutter from cutter jammed.
- Metallic frame mechanism

XP-R330H

Thermal Receipt Printer

QR CODE | EASY LOAD | COMPACT DESIGN | HIGH SPEED | AUTO CUTTER | VARIOUS INTERFACE | PAPER WIDTH

Model	XP-R330H
Printing method	Direct thermal
Paper width	58/80/83±0.5mm
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Column capacity	576 dots/line(adjustable by command)
Printing speed	300 mm/s Max.
Interface	USB+Lan/USB+Serial (Optional : WIFI/Bluetooth)
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE / PDF417
Input buffer	2048 Kbytes
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 100-240V, 50 ~ 60Hz Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	1.115 Kg
Dimensions	133×126×130mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 80%)
Reliability	
Cutter life	2 million cuts
Printer head life	150 KM
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/Android/ Windows

Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

ANDROID iOS Windows Linux