

# Product datasheet

Specifications



## Cat6 Patch Cord UTP 1M CM, Grey

ACTPC6UBCM10GY

### Main

Range	Actassi
Product	Patch cord
Colour	Grey
Cable shielding type	UTP

### Complementary

Type of cable	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Length (customizable value in configurator)	0...1 m
Communication network category	6
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 mOhm
AWG gauge	AWG 24
Attenuation	Guaranteed: 0.1 dB
Far end crosstalk [FEXT]	49.8 dB
Power sum far end crosstalk [PSFEXT]	46.9 dB
Minimum number of matings	1000 cycles
Targeted region	Asia Pacific.

### Environment

Flame retardance	CM
Standards	IEC 60603-7 FCC part 68 subpart F AS/NZS 3080:2003 TIA/EIA-568-B ISO/IEC 11801 2nd edition

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	50.0 g
Package 1 Height	1 cm
Package 1 width	30.2 cm
Package 1 Length	21 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins