

Product data sheet

Specifications



Category6, UTP 24-port Non-Shutter Patch Panel, Loaded



ACTPP6U24NSS

Main

| | |
|---------------------------|----------------------|
| Range of product | Actassi |
| Product or component type | Patch panel |
| Device presentation | Loaded |
| Provided equipment | With RJ45 connectors |

Complementary

| | |
|--------------------------------|---------------------------|
| [In] rated current | 1.5 A |
| Number of port | 24 port of UTP |
| Product compatibility | standard 19" cabinet/rack |
| Communication network category | 6 |
| Contact resistance | 1 mOhm |
| Insulation resistance | >= 200 MOhm |
| Minimum number of matings | 1000 cycles |
| Number of rack unit | 1U |
| Type of connector | S-110 keystone |

Environment

| | |
|---------------------------------------|--|
| Ambient air temperature for operation | -40...70 °C |
| Standards | ANSI/TIA/EIA-568-B ISO/IEC 11801 Ed.2, 2002 |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 1.000 kg |
|------------------|----------|

Offer Sustainability

| | |
|--------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |

| | |
|-----------------------------------|---|
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|
