

Key Features

- Ultra Fine Touch Technology offering up to 40-point touch for a pen-on-paper writing experience
- myViewBoard Whiteboard software with engaging classroom tools
- Screen share via USB-C or wirelessly via myViewBoard Display and ViewBoard Cast with Airplay and Chromecast
- Intuitive remote device control and multimedia broadcast with myViewBoard Manager
- Android 11 OS powered by an octa-core CPU for optimized efficiency and security (Upgradable to Android 13)



Product **Description**

Designed with modern educators in mind, the ViewBoard® 50-5 Series offers an intuitive and interactive interface for a multi-user writing experience. With a single-cable USB-C for instant, worry-free connectivity, teachers can seamlessly plug-in and control their devices while continuing the lesson. Both students and educators enjoy smooth writing with Ultra Fine Touch Technology offering 40-point touch, and the dual-pen that comes in a range of colors and sizes. Rest assured you and your students' eyes are cared for and protected as the ViewBoard® 50-5 Series comes with Flicker-Free technology and an integrated TÜV certified blue light filter for all brightness levels. Fully integrated with the myViewBoard suite, the ViewBoard® 50-5 Series brings together hardware and software for a complete classroom solution. Compatible with a full line of accessories, the ViewBoard® 50-5 Series enables you to effectively teach with a variety of engaging tools.



- 1. Menu Control
- 2. USB 3.0
- 3. USB 2.0
- 4. VESA® Wall Mount (800x600mm)
- 5. RS-232 6. LAN
- 7. AUDIO OUT
- 8. HDMI OUT
- 9. SPDIF 10. OPS Slot
- 11. TOUCH 1
- 12. HDMI 1
- 13. HDMI 2
- 14. HDMI 3

- 15. TOUCH 2
- 16. USB Type-C 17. USB 3.0
- 18. USB 3.0
- 19. USB 2.0
- 20. Wi-Fi Module Slot

Visit Us

www.viewsonic.com

DISPLAY		BUNDLE SOFTWARE	
Panel Size:	86"	Basic Annotation Software:	myViewBoard
Panel Type:	TFT LCD Module with DLED Backlight. IPS	Pro Annotation Software:	myViewBoard for Windows (Embedded in Windows Slot-in PC)
Display Area (mm): Aspect Ratio:	1913.0(H) x 1084.0 (V) 16:9	Wireless Presentation:	vCast/myViewBoard Display App
Resolution:	UHD 3840x2160	SPECIAL FEATURES	
Colors:	1.07B colors (10bit)	All in one LICE parts	"SmartPort™ USB" to all
Brightness:	350 nits (typ.)	All-in-one USB port:	channels.
Contrast Ratio:	1200:1 (typ.) 5000:1 (DCR)	Simple LAN sharing between IFP and slot-in device:	Yes
Response Time:	8ms	Light Sensor:	Yes
Viewing Angles:	H = 178, V = 178 typ.	POWER	
Backlight Life:	50,000 hours (Min)	Voltage:	100-240VAC +/- 10% Wide Range
Surface Treatment:	Hardness: 7H, Anti-glare coating	Consumption: ERGONOMICS	175W(typ.), 0.5W (off)
Bezel:	Slim	Wall Mount (VESA®):	800 mm x 600 mm
Orientation:	Landscape	OPERATING CONDITIONS	
PLATFORM		Temperature (° C):	0°C to 40°C
Processor:	ARM Cortex-A73*4 + Cortex-A53*4	Humidity:	10% ~ 90% RH non- condensing
RAM:	4GB	DIMENSIONS (W X H X D)	
Storage:	32GB	5	77.05 x 45.66 x 3.41 in /
тоисн		Physical (inch / mm):	1957.1 x 1159.8 x 86.5 mm
Type/ Tech:	Ultra Fine Touch Techology (IR Recognition)	Packaging (inch / mm):	83.07 x 50.51 x 8.86 in / 2110 x 1283 x 225 mm
Touch Resolution:	32768 ×32768	WEIGHT	
Tauch Daint	Windows: 40 points of	Net (lb / kg):	147.05lb/66.7kg
Touch Point:	touch, Android : 20 points of touch	Gross (lb / kg):	191.58lb/86.9kg
INPUT		REGULATIONS	
номі:	2.0 x 3 (3840x2160 @60Hz, HDCP2.2, HDMI1 with CEC/ARC)	cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT, Mexico NOM, Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL(Low Blue Light Certification), Flicker Free, Green BOM, RoHS, ErP-Eco, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, PAIA	
RS232:	x1	PACKAGE CONTENTS	
OPS:	x1	1. Power cord	
WiFi:	x 1 module slot	Remote control with AAA battery	
OUTPUT		3. Touch USB cable	
HDMI:	x1 (4K@60Hz)	4. Touch pen x 2	
Audio:	x1 (Earphone out)		
SPDIF:	x1 (optical)	(VB-PEN-009)	
LAN	0	5. Quick Start Guide + Compliance statement	
RJ45:	x2	6. RS232 adapter	
USB	2.0 x 2	7. Clamp x 5	
Type A:	3.0 x 4	8. Camera Plate	
Туре В:	x2, for touch	9. Screw x 8	
Type C:	x1 (DP 1.2, USB2.0, PD65W, Ethernet 100M)	10. HDMI cable	
SPEAKERS		• VPC2-O series	
12W x 2 + 16W x 1 subwoofers		VPC2-O-B series	
TOP CAMERA PLATE		VPC25-W33-O1-1BVPC27-W53-O1-1B	

• VPC12-WPO-17 • VPC12-WPO-18

EMBEDDED OS

Android 11 (Upgradable to Android 13)

 $\label{lem:copyright} \ @\ ViewSonic\ Corporation\ 2000-2024.\ All\ rights\ reserved.$