



Cisco CBS350-16T-2G-EU network switch Managed L2/L3 Gigabit Ethernet (10/100/1000) Silver



Brand : Cisco

Product code: CBS350-16T-2G-EU

Product name : CBS350-16T-2G-EU

Business 350 switch, 16 10/100/1000 ports, 2 Gigabit SFP, internal PSU, EU
Cisco CBS350-16T-2G-EU. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16, Installed SFP modules quantity: 2, USB 2.0 ports quantity: 1. MAC address table: 16000 entries. Network standard: IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3ad. Rack mounting

Management Features		Security	
Switch type *	Managed	DHCP features	DHCP relay, DHCP server, DHCPv6 client
Switch layer	L2/L3	Access Control List (ACL)	✓
Quality of Service (QoS) support	✓	Access Control List (ACL) rules	1024
Web-based management	✓	IGMP snooping	✓
Cloud-managed	✓	Security algorithms	HTTPS, SSH, SSL/TLS
ARP inspection	✓	MAC address filtering	✓
Configuring Location Settings (CLI)	✓	SSH/SSL support	✓
MIB support	✓	Password protection	✓
Ports & interfaces		Multicast features	
Basic switching RJ-45 Ethernet ports quantity *	16	Multicast support	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Protocols	
Installed SFP modules quantity *	2	Management protocols	SNMP
USB 2.0 ports quantity	1	Design	
Network		Rack mounting *	✓
Network standard *	IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3ad	Product colour	Silver
10G support *	✓	Reset button	✓
Port mirroring	✓	LED indicators	✓
Flow control support	✓	Performance	
Link aggregation	✓	Built-in processor	✓
Broadcast storm control	✓	Processor frequency	800 MHz
Auto MDI/MDI-X	✓	Internal memory	512 MB
Spanning tree protocol	✓	Flash memory	256 MB
Head-of-line (HOL) blocking	✓	Firmware upgradeable	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Energy Management	
VLAN support	✓	Power supply included *	✓
Number of VLANs	4094	Operational Conditions	
Data Transmission		Operating temperature range (T-T)	-5 - 50 °C
MAC address table *	16000 entries	Storage temperature range (T-T)	-25 - 70 °C
Jumbo Frames support	✓	Operating relative humidity range	10 - 90%
Jumbo frames	9000	Storage relative humidity range	10 - 90%



889728293587

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-APR-2022. Prints or copies of Information are only valid on the printed Publication date