

Tenda



All for better networking.

AC6

AC1200 Smart Dual - Band WiFi Router



AC6

AC1200 Smart Dual-band WiFi Router

Product Overview

With Gigabit speeds compliant with IEEE802.11ac, the TENDA AC6 smart dual-band WiFi router offers throughput as high as 1167Mbps.


Powered with the latest features including beamforming+ technology and the innovative MU-MIMO, that's just the start. With the 28nm CPU, independent power amplifiers, four 6dBi high-gain antennas, you are assured to have an uninterrupted gaming experience and 4K video streaming.

Tenda's AC6 has great eco credentials too. With a power saving function, App-based management and migration of PPPoE user credentials allows for a smarter and eco-friendly digital life.

Features


- 11ac speed up to 1167Mbps (5GHz: 867Mbps + 2.4GHz: 300Mbps)
- Realtek chipset for stable and fast WiFi connection
- High powered amplifiers and external antennas for whole-home coverage
- Beamforming+ for longer range of IEEE802.11ac-compliant WiFi clients
- Innovative MU-MIMO technology for more connected clients
- Smart WiFi Schedule for lower power consumption
- Migration PPPoE user name and password for hassle-free configuration

Features




5th Generation WiFi: 802.11ac with Dual-band Connectivity

Compliant with IEEE802.11ac, AC6 offers a data rate as high as of 1167Mbps (5GHz: 867Mbps + 2.4GHz: 300Mbps), triple times faster than 11n-compliant routers. Its fast and stable performance makes it the ideal choice for lag-free HD streaming, online gaming and other bandwidth-intensive tasks.




Four 6dBi high-gain antennas for whole-home WiFi coverage

With four 6dBi high-gain antennas that powered by the multi-oscillator radiation technology, AC6 blankets you home with reliable WiFi.



High-powered amplifiers

With the high-powered amplifiers for WiFi on both 2.4GHz and 5GHz bands, Tenda's AC6 delivers a stronger signal through walls, allowing you to enjoy uninterrupted connection in every corner of your home.



28nm CPU for stability


With 28nm CPU, AC6 allows you to enjoy a fast and stable connection throughout your home.

Features



Innovative MU-MIMO technology

The innovative MU-MIMO technology delivered in AC6 allows communication with more wireless devices simultaneously and offers you the fastest possible connection.



Beamforming+ for wider WiFi coverage and internet stability

Beamforming+ technology enables AC6 to lock on to your WiFi receiving clients rather than blast WiFi in all directions, and mitigates co-channel interference, letting you enjoy fast internet connection.



Hassle-free configuration

What if you forget your PPPoE user name or password when replacing your older router? Are you still troubled by complicated setup and configurations?

AC6 allows you to replicate the user name and password provided by your ISP by connecting the WAN port of your old router to the LAN port of AC6, letting you go from laborious configurations.

Specification

AC6 AC1200 Smart Dual-Band WiFi Router

Hardware Specification	
Standards	IEEE802.3; IEEE802.3u
Interface	1*10/100Mbps WAN port 3*10/100Mbps LAN ports
Antenna	4*6dBi external dual band antennas
Button	1*WiFi /RST button
Power	Output: DC 9V==1A
Dimensions	220mm*141.5mm*49mm
Weight	Net weight: 340g ±50g Weight: 700g ±100g
LED Indicator	System*1,WAN*1, LAN*1, WiFi*1
Wireless Features	
Wireless Standards	IEEE 802.11ac/a/n 5GHz; IEEE 802.11b/g/n 2.4GHz
Data Rate	5GHz: Up to 867Mbps 2.4GHz: Up to 300Mbps
Frequency	Simultaneous dual band 2.4GHz(2.412 – 2.472 GHz) & 5GHz(5.150 – 5.350 GHz)
Transmit Power	CE: 2.4G<19.99dbm; 5G<22.99 dbm
Basic Features	SSID Broadcast: Enable/Disable; Transmission Power: High, Medium, Low, Beamforming, MU-MIMO
Wireless Security	WPA-PSK/WPA2-PSK, WPA/WPA2; Wireless Security: Enable/Disable; WPS(WiFi Protected Set-up) fast encryption
Software Features	
Internet Connection Type	PPPoE, Dynamic IP, Static IP PPPoE(Russia), PPTP(Russia), L2TP(Russia)
Operating Mode	Wireless Router Mode Universal Repeater Mode WISP Mode
DHCP Server	DHCP Server DHCP Client List DHCP Reservation
Virtual Server	Port Forwarding DMZ Host UPnP
Security	Client Filter Parental Control(support black list and white list) Remote Web Management

Firewall	Forbid UDP flood attack Forbid TCP flood attack Forbid flood attack Forbid WAN PING from internet
DDNS	Support DynDNS, Oray.com, 88ip
VPN	IPsec pass through PPTP pass through L2TP pass through
Special Features	PPPoE Username/password Clone Smart WiFi Schedule Smart Power Saving Smart LED on/off Tenda Cloud Tenda App
Others	Bandwidth Control(auto/20/40/80 MHz) Guest Network IPTV MAC Clone Static Routing System Log Backup & Restore configurations Firmware upgrade online Firmware upgradeable via browser
Others	
Temperature	Operating Temperature: 0°C ~ 40°C Storage Temperature: -40°C ~ 70°C
Humidity	Operating Humidity:10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing
Factory Default Settings	Default Access: tendawifi.com
Certificates	CE, FCC, RoHS
Package Contents	AC1200 Smart Dual-Band Gigabit WiFi Router Power Adapter Install Guide Ethernet Cable

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

TendaTechnology Bldg.Int' IE-City,
#1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

E-mail:support@tendacom.cn
Tel:+86-755-2765 7098
Fax:+86-755-2765 7178
PC:518055

