



**THERMAL
PRINTER TYPE
SP-POS88V**



MAIN FEATURES:

- High speed of printing up to 250mm/sec.
- Firmware download available.
- 2D barcode printing support.
- Anti-electromagnetic interference level 3

SPECIFICATIONS:

Model No.		SPRT SP-POS88V
Print	Printing Method	Thermal Line
	Printing Speed	250mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
Character	Character Set	ASCII, GB18030(chinese), BIG5
	Print Font	Codepage, ANK:12x24, Chinese: 24x24
	Character per Line	42/48
Paper Spec.	Paper Type	Thermal Paper
	Paper Width	79.5±0.5mm
	Paper Roll Diameter	Max.: 80.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06 – 0.08mm
Power Supply Method		Drop-in easy paper loading
Printer Mechanism		SPRT Brand
Reliability	Mean Cycles Between Failure (MCBF)	60 million lines
	TPH	100Km
Barcode		1D:UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128: 2D:PDF417, QR CODE, DATA matrix
Emulation		ESC/POS
Driver		Windows98/2000/NT/XP/Vista/Win7/Win8/8.1/Linux/Opos
Sensor		Paper end sensor
Drawer Port		1 port
Interface		RS-232/Parallel/USB/WIFI/Ethernet

CELMI s.r.l.

Largo Brugnatelli 13/16 20090 BUCCINASCO (MI) ITALY
 Tel: +39-0245712209 / 0257503712 Fax: +39-0245705836 / 0257506211
 Internet: www.celmi.com mail: info@celmi.com

Power Supply (adapter)		AC100 – 240V±10% (include); DC 24V, 2A
Auto Cutter	Type	Guillotine
	Life	1,000,000 Cuts
	Cutting Method	Partial Cuts
Physical	Net Weight	1,3Kg
	Gross Weight	2,6Kg
	Printer Dimension	139x200x150 mm
	Color	Black/Beige
Environment	Operating Temp.	5 – 50 °C
	Storage Temp.	-20 – 60 °C
	Operating Humidity	10 – 80 %
	Storage Humidity	10 – 90 %
Application		Restaurant, Department stores, Kitchen, Convenience stores, Specialty retail, Supermarket