Godex[®] DT2/DT4/G500 Label Printer 14/1



DT2

APPROVALS



SPECIFICATIONS

Print Speed:

DT2/DT4: 2 to 4 ips G500: 5 ips

Print Length:

Minimum: 0.16 in Maximum: 68 in

Print Width: DT2: 2.12 in

DT4/G500: 4.25 in Media:

Label roll O.D. max: 5.0 in

Real Time Clock: DT2/DT4: standard

Core:

1 in, 1.5 in Thickness: 0.06 to 0.20 mm

Ribbon (G500):

Core: 1 in Length:300 m Max ribbon roll 0.D.: 2.67 in Wide: 1.18 to 4.33 in

STANDARD FEATURES

- · Auto language emulations GEPL, GZPL
- · Free GoLabel design software for EZPL or Q Label
- 203 DPI (8 dot/mm)
- Drop in media loading
- USB or RS-232 interface
- Plain, gap label, black, mark or fanfold label
- Label length detection
- Direct thermal
- Model G500- direct thermal/thermal transfer
- 32 Bit CPU
- Tear bar

Printer Language: GZPL or GEPL

Resident Fonts:

11 resident alphanumeric fonts (included OCR A & B) those are expandable eight times horizontally and vertically. All bit mapped fonts in eight orientations

Bar Codes:

Code 39, Code 93, Code 128 (subset A, B, C,) UCC/ EAN - 128 K-Mart, UCC/EAN - 128, UPC A/E (add on 2 & 5,) 2 of 5, EAN 8/13 (add on 2 & 5.) Codabar, Post Net, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Datamatrix code, QR Code

Dimensions:

DT2: 8.58 (L) x 6.77 (H) x 3.94 in (W) 218 (L) x 172 (H) x 100 mm (H) DT4: 8.58 (L) x 6.53 (H) x 6.61 in (W) 218 (L) x 166 (H) x 168 mm (H) G500: 11.2 (L) x 6.8 (H) x 8.9 in (W) 285 (L) x 171 (H) x 226 mm (H)

Interfaces:

Baud rate 4800 to 115,200; DB9 USB port U2.0

Memory:

4 MB flash - DT2, 8 MB - DT4 and G500

Power:

Auto switching 100/240 VAC 50/60 Hz Environment:

Operation: 41°F to 104°F (5°C to 40°C) Storage: -4°F to 122°F (-20°C to 50°C) Humidity:

Operation: 30 to 85 % non-condensing, free air Storage: 10 to 90% non-condensing, free air

Approvals:

CE (EMC), FCC Class A, CB, CUL, CCC

Warranty:

Two-year limited

686



NEW

Godex[®] DT2/DT4/G500 Label Printer

PART NUMBER/PRICE

PART #	DESCRIPTION	WEIGHT	PRICE
132423	DT2 2 in direct thermal, time & date 10/240 VAC printer	2.65 lb	Consult
132424	DT4 4 in direct thermal, time & date 110/240 VAC printer	3.3 lb	Consult
132425	G500 4 in direct/thermal transfer, 110/240 VAC printer	6 lb	Consult
DT2			
150738	Label peeler		Consult
150739	Cutter		Consult
150740	Print head		Consult
DT4			
150741	Label peeler		Consult
150742	Cutter		Consult
150743	Print head		Consult
107638	Guardian enclosure		Consult
G500			
150744	Label peeler		Consult
150745	Cutter		Consult
150746	Print head		Consult
107639	Guardian enclosure		Consult
Cables For	All Printers		
41276	6 ft serial cable (DB9 M to blunt end)		Consult
79074	USB cable		Consult
64661	6 ft serial cable DB9 M to 8-Pin DIN		Consult
64660	6 ft serial cable DB9 M to DB9 male		Consult
Custom Pin	Custom RS-232 serial cable		Consult

OPTIONS/ACCESSORIES

PART #	DESCRIPTION	PRICE
97370	Label View Pro bar code software, keyless activation	Consult
38941	Cleaning pen for open print head printers 12 per box	Consult
38794	Cleaning cards, 2 in W x 6 in L 25 per box for RL-22DT	Consult
35664	Cleaning cards, 4 in W x 6 in L for RL-42DT and RL-42TT	Consult
111085	Power supply, Rice Lake printers	Consult
Label Stock	/Ribbon	
DT2		
110347	Direct thermal, 2.25 W x 1.25 in L, 5 in diameter with perf., 2100/roll	Consult
40332	Direct thermal, 2.25 W x 2 in L, 5 in diameter with perf., 1445/roll	Consult
110348	Direct thermal, 2.25 W x 3 in L, 5 in diameter with perf., 950/roll	Consult
110349	Direct thermal, 2.25 W x 4 in L, 5 in diameter with perf., 700/roll	Consult
65617	Direct thermal, 2.25 W x 4.5 in L, 5 in diameter with perf., 600/roll	Consult
110346	Direct thermal, 1.20 in x .85 in 5 in diameter with perf., 2710/roll	Consult
47761	Direct thermal, 2.5 W x 121 ft L, continuous 12 rolls/case	Consult
DT4		
53251	Direct thermal, 4 W x 3 in L, 5 in diameter with perf., 930/roll	Consult
40331	Direct thermal, 4 W x 4 in L, 5 in diameter with perf., 745/roll	Consult
37345	Direct thermal, 4 W x 6 in L, 5 in diameter with perf., 450/roll	Consult
G500		
53261	Thermal transfer, 4 W x 3 in L, 5 in diameter with perf., 930/roll	Consult
110536	Ribbon (black),4.3 in wax/resin, 984 ft length	Consult
110537	Ribbon (black),2.5 in wax/resin, 984 ft length	Consult

