



# AC 750

Wireless Dual Band Gigabit ADSL2+ Modem Router Archer D2

#### Highlights

- 750Mbps Wireless Speed 300Mbps on 2.4GHz + 433Mbps on 5GHz
- Broad Coverage 3 external detachable antennas provide maximum omni-directional wireless coverage and reliability
- Beamforming Technology 2.4 GHz supporting Beamforming technology brings better range and performance
- · Gigabit Wired Speed Full Gigabit ports ensure ultrafast data transfers
- · ADSL/EWAN Allows users to have flexibility of different Internet connections among ADSL/VDSL, cable or fiber modem
- · USB Port Easily share printers, files or media with your friends or family locally or over the Internet
- Tether App TP-LINK Tether provides the easiest way to access and manage the router on your iOS and Android devices













USB







Beamforming Technology


2.4 & 5 GHz

433Mbps

2.0 Port

Tether

## Features



## Speed

- 750Mbps Wireless Speed Combined wireless speeds up to 750Mbps at 2.4GHz & 5GHz band concurrently
- Support 802.11 ac Offering 3 times faster data rate than 802.11n in a single stream
- Gigabit Wired Speed Full Gigabit ports ensure ultrafast data transfer speeds



## Wi-Fi Range

- 3 External Detachable Antennas 3 external detachable antennas provide maximum omni-directional wireless coverage
- Beamforming Technology Archer D2's 2.4GHz band supports beamforming technology, extending wireless coverage by boosting signal strength



## Reliability

- Simultaneous Dual Band Reduces interference for more stable connections
- QoS Advanced QoS automatically recognizes & prioritizes streaming & gaming applications

## Features



## Easy Sharing

- USB Port for Fast Sharing With one USB 2.0 port, you can access and share a printer as well as your files and media locally. Via the router's FTP server, you can also have access to your files & media with networked devices remotely
- Built-in Print Server Supports wireless printing from multiple computers (works in conjunction with a USB Printer)
- Built-in Media Server Allows users to play music, video and view photos



### Ease of Use

- Hassle-free Management with Tether App –
   Tether App allows easy network management at your fingertips
- 3-Step Quick Installation Easy Setup Assistant supporting multiple languages provides a quick & hassle free installation
- Built-in Intelligent Auto-detection Automatically figuring out which connection type to use in a flash, saving the trouble of searching for connection information
- Fast Encryption Easy one-touch WPA wireless security encryption with the WPS button




## Security

- Guest Network Access Guest Network Access provides secure Wi-Fi access for guests
- Parental Control Establish restricted access policies for all connected devices
- Easy Bandwidth Management IP-based Bandwidth Control makes it easier for you to manage the bandwidth of connected devices
- VPN Support Secure access to your home or office network from remote devices
- SPI and NAT Firewall Protects end-user devices from potential attacks from the Internet

### Beamforming Technology For Laser-Focused Wi-Fi

Beamforming concentrates the Wi-Fi signal towards your devices, focusing the data transmission toward the most-needed directions. Superior Wi-Fi bandwidth utilization increases Wi-Fi range, delivering highly targeted and efficient Wi-Fi connections.



# Tether App Easy Network Management at Your Fingertips


TP-LINK Tether provides the easiest way to access and manage the router on your iOS and Android devices. From Setup to Parental Control, Tether provides a simple, intuitive user interface to see what the status of your router is, who's online and what their privileges are. TP-LINK Tether is going to be adaptable to more router models.



# Specifications

#### Hardware

- Ethernet Ports: 3 10/100/1000Mbps RJ45 LAN Ports, 1 10/100/1000Mbps RJ45 WAN/LAN Port, 1 RJ11 Port
- · USB Ports: One USB 2.0 Port
- · Button: WPS Button, Reset Button, Wireless On/Off Button, Power On/Off Button
- External Power Supply: 12V/1.5A
- **Dimensions (W x D x H):**  $9.0 \times 6.3 \times 1.5 \text{ in.} (229 \times 160 \times 37 \text{mm})$
- IEEE Standards: IEEE 802.3, 802.3u, 802.3ab
- ADSL Standards: Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT),
   ITU-T G.994.1 (G.hs), ITU-T G.995.1
- · ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis),
- ADSL2+ Standards: ITU-T G.992.5
- · Antenna Type: 3 external detachable antennas (RP-SMA)
- Antenna Gain: 3 x 2dBi for 2.4GHz and 3 x 3dBi for 5GHz



#### Wireless

- · Wireless Standards: IEEE 802.11n/g/b 2.4GHz, IEEE 802.11ac/n/a 5GHz
- Frequency: 2.4GHz and 5GHz
- · Signal Rate: 300Mbps at 2.4GHz, 433Mbps at 5GHz
- Transmit Power: CE: <20dBm(2.4GHz, EIRP), <23dBm(5GHz, EIRP)
- Wireless Function: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
- Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA-PSK2 encryptions, Wireless MAC Filtering
- · Wireless Schedule: Support 2.4GHz and 5GHz Wireless Schedule

# Specifications

#### Software

- · Operation Modes: ADSL Modem Router, Wireless Router
- · DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP Relay
- · Quality of Service: ATM QoS, Traffic Control(IP QoS)
- · Port Forwarding: Virtual Server, Port Triggering, DMZ, ALG, UPnP
- Dynamic DNS: DynDns, NO-IP
- · VPN Passthrough: PPTP, L2TP, IPSec Passthrough
- ATM/PPP Protocols: ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364),
   PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MER\IPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC Up to 8 PVCs
- Security: NAT Firewall, Access Control, MAC / IP / URL Filtering, IP and MAC Address Binding
- Advanced Functions: Parental Control, Network Address Translation(NAT), Port Mapping(Grouping), Static Routing, RIP v1/v2(optional), DNS Relay, DDNS, IGMP V1/V2/V3
- USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
- Management: Web Based Configuration(HTTP), Remote management, command Line Interface, SSL for TR-069, SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic Tools
- Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1
- IPSec VPN: Supports up to 10 IPSec VPN tunnels
- Protocols: Supports IPv4 and IPv6

### Others

#### **Package Contents**

- · AC 750 Wireless Dual Band Gigabit ADSL2+ Modem Router Archer D2
- · External Splitter
- · RJ-11 Telephone Cable
- · RJ-45 Ethernet Cable
- · Resource CD
- · Power Adapter
- · Quick Installation Guide

#### Certification

· CE, RCM, RoHS

#### System Requirements


- Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, MAC OS, NetWare, UNIX or Linux
- · Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser
- · Cable or DSL Modem
- · Subscription with an Internet Service Provider (for Internet access)


#### **Environment**

- · Operating Temperature:  $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$  (32 °F ~ 104 °F)
- Storage Temperature:  $-40^{\circ}\text{C} \sim 70^{\circ}\text{C} (-40^{\circ}\text{F} \sim 158^{\circ}\text{F})$
- · Operating Humidity: 10%~90% non-condensing
- · Storage Humidity: 5%~90% non-condensing

## Others

#### Ideal to use with





### Similar Products











🗱 🖪 For more information, please visit

http://www.tp-link.com/en/products/details/?categoryid=&model=Archer+D2

or scan the QR code left

Specifications are subject to change without notice. TP-LINK is a registered trademark of TP-LINK Technologies CO., Ltd. Other brands and product names are trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies CO., Ltd.

www.tp-link.com