

Product datasheet

Specifications



APC Easy UPS 1 Ph Line Interactive, 1500VA, Tower, 230V, 4 Schuko CEE 7 outlets, AVR, LCD

SMV1500AI-GR

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Input voltage	220 V 240 V
Main Output Voltage	230 V
Rated power in W	1050 W
Rated power in VA	1500 VA
Input Connection Type	IEC 60320 C14
Output connection type	4 Schuko CEE 7
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Documentation CD User manual USB cable

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery voltage	24 V
Battery charger power	54 W rated
Battery life	3...5 year(s)
Replacement battery	APCRBCV207 ↗
Extended runtime	0

General

Number of power module free slots	0
Number of power module filled slots	0

Redundant	No
UPS size	WS
Physical	
Colour	Black
Height	22 cm
Width	16 cm
Depth	41 cm
Product weight	17.8 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Input	
Network frequency	45...65 Hz auto-sensing
Input voltage limits	165...290 V
Output	
Maximum configurable power in W	1050 W
Output frequency	50/60 Hz +/- 1 Hz unsynchronised
Crest factor	3 : 1
UPS type	Line interactive
Wave type	Sine wave
Graph display	1
Maximum configurable power in VA	1500 VA
Transfer time	2-6 ms typical : 12 ms maximum
Conformance	
Product certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Environmental	
Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-10...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	45 dBA
IP degree of protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

Surge Protection and Filtering

Surge energy rate	190 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33.9 cm
Package 1 Width	27.2 cm
Package 1 Length	50.8 cm
Package 1 Weight	20.75 kg

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)