



Thermal Receipt Printer


M817

- 200mm/s, 260mm/s low noise, high speed printing.
- Cash drawer driver.
- Sound and light alarm.
- Support OPOS and Linux.
- Support auto cutter, wall mounting capable.
- Support printer head over-temperature protection, longer life.



M817

Thermal Receipt Printer



MODEL	M817			
Printing method	Direct thermal			
Printing speed	300mm/s	260mm/s	230mm/s	200mm/s
Interface type	USB+Serial+Lan	USB+Serial+Lan	USB+Parallel / USB+Serial / USB+Lan	USB /Lan
Paper width	79.5 ± 0.5mm			
Printable area	72mm(adjustable by commands)			
Maximum paper diameter	Φ80 mm			
Paper thickness	0.06-0.08mm			
Column capacity	576 / 512 dots/line			
Line space	3.75mm(Changeable by commands)			
Commands	Compatible with ESC/POS			
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots			
Dimension	192×145×143 mm (D×W×H)			
Gross weight	1.06 kg			
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128			
2-dimension code	QR CODE / PDF417 (U+S+L, U+L)			
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)			
Cutter	Partial			
Cutter life	1.5 million cuts			
Print head life	100KM			
Input buffer	2048 Kbytes	64 Kbytes	64 Kbytes	64 Kbytes
NV Flash	256 Kbytes			
Power adaptor	AC110V/220V, 50~60Hz			
Power source	DC 24V/2.5A			
Cash drawer output	DC 24V/1A			
Work environment	Temperature: 0~45℃, humidity: 10~80RH%			
Storage environment	Temperature: -10~60℃ , humidity: 10~90RH%			
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux			

