

# ViewSonic® LCD DISPLAY VP2756-2K

## Key Features

- **Lifelike True Beauty:** International color standard Pantone validated and 100% sRGB wide color gamut
- **Precise Color:** ColorPro Verified with pre-factory calibration for overwhelmed Delta E < 2 color accuracy
- **Multimedia Devices:** Support USB-C with 60W high-speed charging, plus HDMI 1.4, DisplayPort 1.2a, USB 3.2
- **Unlimited Flexibility:** Auto Pivot & Ergonomic Stand with tilt, swivel, pivot, and height adjustments
- **The Visible Difference:** 2K QHD(2560\* 1440 ) resolution IPS panel with 27" frameless design



## Product Description

Designed with creative professionals in mind, the ViewSonic VP2756-2k delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

**Visit Us** [www.viewsonic.com](http://www.viewsonic.com)

|  |  |                               |   |
|--|--|-------------------------------|---|
| DISPLAY  |  | ADDITIONAL HARDWARE           |   |
| Display Size (in.):                              | 27   | Kensington Lock Slot:         | 1   |
| Viewable Area (in.):                             | 27   | Cable Organization:           | Yes   |
| Panel Type:                                      | IPS Technology   | CONTROLS                      |   |
| Resolution:                                      | 2560 x 1440  | Physical Controls:            | Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)  |
| Resolution Type:                                 | QHD (Quad HD)  | On Screen Display:            | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu   |
| Static Contrast Ratio:                           | 1,000:1 (typ)  | OPERATING CONDITIONS          |   |
| Dynamic Contrast Ratio:                          | 20M:1  | Temperature:                  | 32°F to 104°F (0°C to 40°C)   |
| Light Source:                                    | LED  | Humidity (non-condensing):    | 20% to 90%  |
| Brightness:                                      | 350 cd/m² (typ)  | WALL MOUNT                    |   |
| Colors:  | 16.7M  | VESA Compatible:              | 100 x 100 mm  |
| Color Space Support:                             | 8 bit true   | INPUT SIGNAL                  |   |
| Aspect Ratio:                                    | 16:9   | Frequency Horizontal:         | 15 ~ 130KHz   |
| Response Time (Typical GTG):                     | 5ms  | Frequency Vertical:           | 24 ~ 75Hz   |
| Response Time (GTG w/OD):                        | 5ms  | VIDEO INPUT                   |   |
| Viewing Angles:                                  | 178° horizontal, 178° vertical   | Digital Sync:                 | TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C   |
| Backlight Life (Hours):                          | 30000 Hrs (Min)  | ERGONOMICS                    |   |
| Curvature:                                       | Flat   | Height Adjust (mm):           | 130   |
| Refresh Rate (Hz):                               | 60   | Swivel:                       | 120°  |
| Blue Light Filter:                               | Yes  | Tilt (Forward/Back):          | -5° / 21°   |
| Flicker-Free:                                    | Yes  | Pivot (Right/Left):           | 90° / 90°   |
| Color Gamut:                                     | Adobe RGB: 81% size / 78% coverage (Typ)<br>DCI-P3: 81% size / 81% coverage (Typ)<br>EBU: 108% size / 99% coverage (Typ)<br>REC709: 110% size / 100% coverage (Typ)<br>SMPTE-C: 118% size / 100% coverage (Typ)<br>NTSC: 78% size (Typ)<br>sRGB: 110% size / 100% coverage (Typ) | WEIGHT (IMPERIAL)             |   |
| Pixel Size:                                      | 0.233 mm (H) x 0.233 mm (V)  | Net (lbs):                    | 15.1  |
| Surface Treatment:                               | Anti-Glare, Hard Coating (3H)  | Net Without Stand (lbs):      | 9.8   |
| COMPATIBILITY                                    |  | Gross (lbs):                  | 21  |
| PC Resolution (max):                             | 2560x1440  | WEIGHT (METRIC)               |   |
| Mac® Resolution (max):                           | 2560x1440  | Net (kg):                     | 6.9   |
| PC Operating System:                             | Windows 10/11 certified; macOS tested  | Net Without Stand (kg):       | 4.4   |
| Mac® Resolution (min):                           | 2560x1440  | Gross (kg):                   | 9.5   |
| CONNECTOR  |  | DIMENSIONS (IMPERIAL) (WXHxD) |   |
| USB 3.2 Type A Down Stream:                      | 2  | Packaging (in.):              | 29.1 x 18.3 x 8.9   |
| USB 3.2 Type B Up Stream:                        | 1  | Physical (in.):               | 24.1 x 16.15~21.27 x 8.5  |
| USB 3.2 Type C Up Stream; DisplayPort Alt mode : | 1  | Physical Without Stand (in.): | 24.1 x 14.3 x 2.1   |
| HDMI 1.4:  | 1  | DIMENSIONS (METRIC) (WXHxD)   |   |
| DisplayPort:                                     | 1  | Packaging (mm):               | 740 x 465 x 225   |
| Power in:  | 3-pin Socket (IEC C14 / CEE22)   | Physical (mm):                | 613 x 410.31~540.31 x 215   |
| AUDIO  |  | Physical Without Stand (mm):  | 613 x 363 x 53  |
| Internal Speakers:                               | 2Watts x2  | GENERAL                       |   |
| POWER  |  | Regulations:                  | cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI                                    |
| Eco Mode (Conserve):                             | 16.5W  | PACKAGE CONTENTS:             | VP2756-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1 |
| Eco Mode (optimized):                            | 19.3W  | Recycle/Disposal:             | Please dispose of in accordance with local, state or federal laws.  |
| Consumption (typical):                           | 22.5W  | Warranty:                     | *Warranty offered may differ from market to market  |
| Consumption (max):                               | 34W  | Power Management:             | Energy Star standards, EPEAT  |
| Voltage:   | AC 100-240V  |                               |   |
| Stand-by:  | 0.3W   |                               |   |
| Power Supply:                                    | Internal Power Supply  |                               |   |

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.