Product datasheet





Easy UPS 3S 30kVA 400V 3:3 UPS, 2 internal 7Ah modular battery strings, expandable to 4

E3SUPS30KHB1

Overview

Presentation	Easy-to-install, easy-to-operate, easy-to-maintain, and easy-to-service 30 kVA, 400V 3-phase UPS. With advanced product features, competitive specifications, and robust electrical design, the Easy UPS 3S UPS makes business continuity easy for small and medium data centers and electrical rooms. Includes dust filter and conformance-coated boards for harsh environments, and 2 internal 7Ah modular battery strings, expandable to 4 strings for extended runtime.
Lead Time	Usually Ships within 6 Weeks
Main	
Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated Power In W	30 kW

Batteries & Runtime

Rated Power In Va

Provided Equipment

Efficiency	View Efficiency Graph ☐
Battery Type	VRLA
Battery Voltage	240 V
Maximum Short-Circuit Current	10 kA
Number Of Battery Filled Slots	2
Number Of Battery Free Slots	2

Physical

Colour	White (RAL 9003)
Height	140 cm
Width	50 cm
Depth	96.9 cm
Net Weight	584 kg
Usb Compatible	Yes

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

30 kVA

Dust filter Installation guide

Input

· · · · · · · · · · · · · · · · · · ·	
Maximum Input Current	55 A
Input Harmonic Distortion	Less than 3 % for full load
Load Power Factor	0.9 leading to 0.9 lagging
Input Power Factor At Full Load	0.99
Input Voltage Limits	304477 V
Network Frequency	4565 Hz

Output

•		
Maximum Configurable Power In Va	30 kVA	
Maximum Configurable Power In W	30 kW	
Output Frequency	50 Hz sync to mains 60 Hz sync to mains	
Harmonic Distortion	Less than 3 %	
Output Harmonic Distortion	< 3% linear load	
Output Voltage Tolerance	+/- 1.5 %	
Ups Type	Double conversion online	
Additional Information	UPS weight does not include battery weight.	

Conformance

Product Certifications	CE	
	EAC	
	RCM	

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 % non-condensing
Operating Altitude	03333 ft
Ambient Air Temperature For Storage	-1540 °C
Storage Relative Humidity	095 % non-condensing
Storage Altitude	0.0015240.00 m
Acoustic Level	63 dBA
Heat Dissipation	1410 W
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	164 cm
Package 1 Width	111.4 cm
Package 1 Length	68.3 cm
Package 1 Weight	638 kg

Contractual warranty

Warranty

Feb 12, 2024

1 year on-site repair or replace with factory authorized Start-Up

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration	
Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)		
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	