

Product datasheet

Specifications



APC Back-UPS Pro, 2200VA/
1320W, Tower, 230V, 4x Schuko
and 2x IEC C13 outlets, RGB
Lights, Pure Sine Wave, Midnight
(Black)

BGM2200B-GR

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Other Input Voltage	230 V
Rated Power In W	1320 W
Rated Power In Va	2200 VA
Product Or Component Type	Uninterruptible power supply (UPS)
Number Of Rack Unit	0U
Cable Length	1.52 m
Number Of Cables	1
Battery Type	VRLA

Batteries & Runtime

Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	1
Number Of Battery Free Slots	0
Battery Recharge Time	16 h
Overcurrent Protection	15 A
Battery Life	3...5 year(s)

General

Product Web Sub-Family	Gaming performance
Max Runtime	0.9 min
Number Preinstalled Power Module	0
Number Of Power Module Free Slots	0
Redundant	No

Physical

Height	292.10 mm
Width	104.14 mm
Depth	408.94 mm

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net Weight	12.34 kg
Mounting Support	Floor
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	Yes
Mounting Position	Vertical

Input

Plug Standard	Schuko
Maximum Input Current	12 A
Switching Current Capacity	15 A
Input Harmonic Distortion	Less than 3 % for full load
Input Protection Type	Circuit breaker

Output

Maximum Configurable Power In W	1320 W
Ups Type	Line interactive
Wave Type	Sine wave
Maximum Configurable Power In Va	2200 VA
Runtime At 100W	00:59:00
Runtime At 200W	00:40:00
Runtime At 300W	00:24:00
Runtime At 400W	00:17:00
Runtime At 500W	00:12:00
Runtime At 600W	00:09:30
Runtime At 700W	00:07:00
Runtime At 800W	00:05:30
Transfer Time	8 ms typical : 10 ms maximum

Conformance

Product Certifications	IEC 62040-1-1 IEC 62040-2
------------------------	------------------------------

Environmental

Ambient Air Temperature For Operation	0...40 °C
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...40 °C
Storage Altitude	0.00...3048.00 m
Acoustic Level	45 dBA

Communications & Management

Free Slots	0
Control Panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge Energy Rate	1080 J
Noise Suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping response time: instantaneous

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	35.5 cm
Package 1 Length	48 cm
Package 1 Weight	14.52 kg

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information