



## TS-1263XU-RP-4G

CPU	AMD G-Series GX-420MC quad-core 2.0 GHz processor
-----	---

CPU Architecture	64-bit x86
------------------	------------

Floating Point Unit	Yes
---------------------	-----

Encryption Engine	Yes (AES-NI)
-------------------	--------------

System Memory	4 GB SO-DIMM DDR3L (1 x 4 GB)
---------------	-------------------------------

Maximum Memory	16 GB (2 x 8 GB)
----------------	------------------

Memory Slot	2 x SO-DIMM DDR3L
-------------	-------------------

Flash Memory	512 MB (Dual boot OS protection)
--------------	----------------------------------

Drive Bay	12 x 3.5-inch SATA 6Gb/s, 3Gb/s
-----------	---------------------------------

Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
---------------------	--

Hot-swappable	Yes
---------------	-----

M.2 SSD Slot	Optional via a PCIe adapter
--------------	-----------------------------

SSD Cache Acceleration Support	Yes
--------------------------------	-----

Gigabit Ethernet Port (RJ45)	4
------------------------------	---

10 Gigabit Ethernet Port	1 x 10GBASE-T (10G/5G/2.5G/1G/100M)
--------------------------	-------------------------------------

Wake on LAN (WOL)	Yes
-------------------	-----

Jumbo Frame	Yes
-------------	-----

PCIe Slot	1 Slot 1: PCIe Gen 2 x4
-----------	----------------------------

USB 2.0 port	2
--------------	---

USB 3.2 Gen 1 port	2
--------------------	---

USB 3.2 Gen 2 (10Gbps) Port	Optional via a PCIe adapter
Form Factor	2U Rackmount
LED Indicators	HDD 1-12, Status, LAN, USB, Power
Buttons	Power, Reset
Dimensions (HxWxD)	89 × 482 × 534 mm
Weight (Net)	16.14 kg
Weight (Gross)	18.98 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	300W (x2) PSU, 100 - 240V
Power Consumption: HDD Sleep Mode	57.15 W
Power Consumption: Operating Mode, Typical	143.17 W
Sound Level	39.2 db(A)
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS)	800

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.