



CPU Architecture 64-bit x86 Graphic Processors Intel® HD Graphics 600 Floating Point Unit Yes Encryption Engine Yes (AES-NI) Hardware-accelerated Transcoding System Memory 4 GB SO-DIMM DDR4 (1 x 4 GB) Maximum Memory 8 GB (2 x 4GB) Memory Slot 2 x SO-DIMM DDR4 Flash Memory 4GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2 (also support 10M) Wake on LAN (WOL) Yes	TS-453DU-RP-4G	
Graphic Processors Intel® HD Graphics 600 Floating Point Unit Yes Encryption Engine Yes (AES-NI) Hardware-accelerated Transcoding System Memory 4 GB SO-DIMM DDR4 (1 x 4 GB) Maximum Memory 8 GB (2 x 4GB) Memory Slot 2 x SO-DIMM DDR4 Flash Memory 4 GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA holid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/1000M)	CPU	Intel® Celeron® J4125 4-core/4-thread processor, burst up to 2.7 GHz
Floating Point Unit Yes Encryption Engine Yes (AES-NI) Hardware-accelerated Transcoding System Memory 4 GB SO-DIMM DDR4 (1 x 4 GB) Maximum Memory 8 GB (2 x 4GB) Memory Slot 2 x SO-DIMM DDR4 Flash Memory 4GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Yes Support 2.5 sigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	CPU Architecture	64-bit x86
Encryption Engine Yes (AES-NI) Hardware-accelerated Transcoding System Memory 4 GB SO-DIMM DDR4 (1 x 4 GB) Maximum Memory 8 GB (2 x 4GB) Memory Slot 2 x SO-DIMM DDR4 Flash Memory 4GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	Graphic Processors	Intel® HD Graphics 600
Hardware-accelerated Transcoding System Memory 4 GB SO-DIMM DDR4 (1 x 4 GB) Maximum Memory 8 GB (2 x 4GB) Memory Slot 2 x SO-DIMM DDR4 Flash Memory 4GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M)	Floating Point Unit	Yes
System Memory 4 GB SO-DIMM DDR4 (1 x 4 GB) Maximum Memory 8 GB (2 x 4GB) Memory Slot 2 x SO-DIMM DDR4 Flash Memory 4GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	Encryption Engine	Yes (AES-NI)
Maximum Memory 8 GB (2 x 4GB) Memory Slot 2 x SO-DIMM DDR4 Flash Memory 4GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support Yes 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)		Yes
Memory Slot 2 x SO-DIMM DDR4 Flash Memory 4GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	System Memory	4 GB SO-DIMM DDR4 (1 x 4 GB)
Flash Memory 4GB (Dual boot OS protection) Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2 (also support 10M)	Maximum Memory	8 GB (2 x 4GB)
Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	Memory Slot	2 x SO-DIMM DDR4
Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	Flash Memory	4GB (Dual boot OS protection)
3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives Hot-swappable Yes M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	Drive Bay	4 x 3.5-inch SATA 6Gb/s, 3Gb/s
M.2 Slot Optional via a PCIe adapter SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives
SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	Hot-swappable	Yes
2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (also support 10M)	M.2 Slot	Optional via a PCIe adapter
(2.5G/1G/100M)		Yes
Wake on LAN (WOL) Yes		2 (also support 10M)
	Wake on LAN (WOL)	Yes
Jumbo Frame Yes	Jumbo Frame	Yes
PCIe Slot 1 Slot 1: PCIe Gen 2 x2	PCIe Slot	
USB 2.0 port 2	USB 2.0 port	2

USB 3.2 Gen 1 port	2
USB 3.2 Gen 2 (10Gbps) Port	Optional via a PCIe adapter
HDMI Output	1, HDMI 1.4b
Form Factor	1U Rackmount
LED Indicators	HDD 1-4, Status, LAN, Expansion, Power
Buttons	Power, Reset
Dimensions (HxWxD)	43.3 × 482.6 × 508.7 mm
Weight (Net)	8.12 kg
Weight (Gross)	10.1 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	250W (x2), 100-240V
Power Consumption: HDD Sleep Mode	30.207 W
Power Consumption: Operating Mode, Typical	45.3 W
Fan	2 x 40mm, 12VDC
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	1500

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.

^{*} Sound Level Test