



QSW-804-4C (EOL)	
Management Type	Unmanaged
Number of Ports	8
10GbE SFP+	4
10GbE SFP+/RJ45 Combo Ports	4
Power Supply Description	Internal Open Frame
Max. Power Consumption	41W
Input Power Type	AC
Input Voltage Range	100-240VAC, 50/60 Hz
MAC Address Table	27K
Total Non-Blocking Throughput	80Gbps
Switching Capacity	160Gbps
Console	RS232
Energy Efficient Ethernet (IEEE 802.3az complaint)	Yes
Fan	System: 2 x 4 cm (12V DC)
Supported Standards	IEEE 802.3ab 1000BASE-T Gigabit Ethernet IEEE 802.3bz 2.5G/5G BASE-T Multi-Gig Ethernet IEEE 802.3an 10GBASE-T 10G Ethernet IEEE 802.3ae 10GBASE-SR IEEE 802.3ae 10GBASE-LR IEEE 802.3x Full-duplex flow control IEEE 802.3az Energy Efficient Ethernet
Form Factor	Desktop
LED Indicators	Per Port: Speed/Link/Activity Per System: Power/Status
Dimensions (HxWxD)	43 × 285 × 233 mm

Weight (Net)	2.1 kg
Weight (Gross)	2.15 kg
Operating Temperature	0°C to 40°C (32°F to 104°F)
Relative Humidity	10% to 85% RH non-condensing
Certifications	CE, FCC, VCCI, BSMI RCM, CCC
Electromagnetic Compliance	CLASS A, UL62368
Jumbo Frames	9k
Warranty	2 Years